


Material Safety Data Sheet



NFPA



HMIS

| | |
|---------------|---|
| Health Hazard | 0 |
| Fire Hazard | 1 |
| Reactivity | 0 |

Issuing Date 28-June-2010

Revision Date 28-June-2010

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name O'REILLY MULTI-PURPOSE GL-5 GEAR LUBRICANT 80W90 AND 85/140
Product Code
Recommended Use
Manufactured by: Omni Specialty Packaging
 10399 S. Hwy 1
 Shreveport, LA 71105
 Phone: 1 (318) 524-1100
Emergency Telephone Number CHEMTREC
 1 (800) 424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance Amber Liquid **Physical State** Liquid **Odor** Mild petroleum odor

Potential Health Effects

Principal Routes of Exposure Eye contact, Skin contact, Inhalation, Ingestion

Acute Toxicity

Eyes
Skin
Inhalation

Ingestion

Eye contact may result in slight irritation and redness.
 Minimally irritating upon direct contact.
 Low hazard at standard temperatures and pressures. Inhalation of oil mist or fumes can cause irritation of the nose, throat and upper respiratory tract
 Do not ingest. May cause nausea, vomiting/diarrhea.

Other

On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually

asymptomatic as a result of repeated small aspirations.

Chronic Effects

Prolonged exposure may cause chronic effects.

Aggravated Medical Conditions

Personnel with pre-existing skin disorders should avoid contact with this product.

Environmental Hazard

See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula

Mixture

| Chemical Name | CAS-No | Weight % |
|--|------------|----------|
| Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) | 64742-65-0 | 40-85 |
| Hydrotreated Distillates, Heavy Paraffinic | 64742-54-7 | 5-25 |
| Additive Package | Mixture | 10-40 |
| Pour Point Depressant | N/A | 0-5 |

4. FIRST AID MEASURES

Eye Contact

Flush with large amount of water for 15 minutes. Get medical attention if eye irritation develops or persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes. Get medical attention immediately if skin discoloration occurs.

Inhalation

If affected, remove individual to fresh air. If not breathing, give mouth-to-mouth resuscitation. Get medical attention if symptoms develop or persist.

Ingestion

CALL PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious person. Don't induce vomiting except at the instructions of the physician.

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties

Not flammable.

Flash Point

430°F

Suitable Extinguishing Media

Water Fog. Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable Extinguishing Media

Water stream may spread fire.

Hazardous Combustion Products

Decomposition and combustion products may include smoke, carbon dioxide, carbon monoxide, and other low molecular weight hydrocarbons.

Explosion Data

Sensitivity to Mechanical Impact
Sensitivity to Static Discharge

Not sensitive.
Not sensitive.

Protective Equipment and Precautions for Firefighters

Wear positive pressure self-contained breathing apparatus (SCUBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal flash point.

NFPA Health Hazard 0 Flammability 1 Reactivity 0 Physical and Chemical Hazards -

6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal Precautions | Use personal protective equipment. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. |
| Methods for Containment | Dike far ahead of liquid spill for later disposal. |
| Methods for Cleaning Up | Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material. |
| Evacuation Procedures Large Spill Fire | Consider initial downwind evacuate for at least 300 meters (1000 feet). If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. |
| Reporting Requirements | Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)546-2972. Check with your local and state regulators regarding their reporting requirements. |

7. HANDLING AND STORAGE

| | |
|-----------------|---|
| Handling | Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids. |
| Storage | Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|--------------------------------|--------------------------|-------------------------|
| Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) 64742-65-0 | 5 mg/m ³ TWA (mist) | 5 mg/m ³ mist | 2,500 mg/m ³ |
| Hydrotreated Distillates, Heavy Paraffinic 64742-54-7 | 5 mg/m ³ TWA (mist) | 5 mg/m ³ mist | 2,500 mg/m ³ |

| | |
|--------------------------------------|---|
| Engineering Measures | Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended limits. |
| Personal Protective Equipment | |
| Eye/Face Protection | Safety glasses or face shield where splashing is possible. Full face-shield to be worn during emergencies. |
| Skin and Body Protection | As needed to prevent repeated skin contact. Solvent resistant gloves should be used if needed. |
| Respiratory Protection | Not normally needed. During emergencies wear respirator. |
| Hygiene Measures | Remove and wash contaminated clothing before re-use. Wash hands before breaks and immediately after handling the product. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|----------------------------|---------------|-----------------------------------|---------------------|
| Appearance | Amber Liquid | Odor | Mild petroleum odor |
| Physical State | Liquid | pH | N/A |
| Flash Point | 430°F | Autoignition Temperature | 729°F |
| Boiling Point/Range | 829°F | Melting Point | 32°F |
| Explosion Limits | N/A | Flammability Limits in Air | N/A |
| Specific Gravity | 0.89 | Solubility | Negligible |
| Evaporation Rate | N/A | Vapor Pressure | N/A |
| Vapor Density | Not Determine | Density | N/A |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Stability | Stable under recommended storage conditions. |
| Incompatible Products | Open Flame and strong oxidizing agents. |
| Conditions to Avoid | Heat, flames, and sparks. |
| Hazardous Decomposition Products | Decomposition and combustion products may include smoke, carbon dioxide, carbon monoxide, and other low molecular weight hydrocarbons. |
| Hazardous Polymerization | None under normal processing. |

11. TOXICOLOGICAL INFORMATION**Acute Toxicity**

| | |
|---------------------------------|---|
| Product Information | Test on similar materials show a low order of acute oral and dermal toxicity. |
| Acute Oral Effects | Test on similar materials indicates low order of acute toxicity. |
| Acute Inhalation Effects | Low acute toxicity expected on inhalation. |
| Skin Effects | Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies. |
| Eye Irritation | Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products. |

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|--|-----------------|--------------------|----------------------------|
| Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) 64742-65-0 | Rat >2000 mg/kg | Rabbit >2000 mg/kg | Rat > 2.18 mg/L 4 hours |
| Hydrotreated Distillates, Heavy Paraffinic 64742-54-7 | | | |

Chronic Toxicity

| | |
|-----------------------------|--|
| Chronic Toxicity | Prolonged exposure may cause chronic effects. |
| Carcinogenicity | Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt% |
| Target Organ Effects | Respiratory system, Eyes, Skin, |
| Genotoxicity | This product is considered non-mutagenic and has negative potential for tumor development based on from Modified Ames Assay, with Mutagenic Index of less than |

1.0.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

| Chemical Name | Toxicity to Algae | Toxicity to Fish | Microtox | Daphnia Magna (Water Flea) |
|--|-------------------|------------------|----------|----------------------------|
| Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5 | | | | |
| Hydrotreated Distillates, Heavy Paraffinic 64742-54-7 | | | | |

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with local regulations. Keep this product out of sewers and waterways.

Contaminated Packaging Dispose of in accordance with local regulations.

| Chemical Name | RCRA – Halogenated Organic Compounds | RCRA – P Series Wastes | RCRA – F Series Wastes | RCRA – K Series Wastes |
|---------------|--|--|--|--|
| | Does not meet hazardous waste criteria | Does not meet hazardous waste criteria | Does not meet hazardous waste criteria | Does not meet hazardous waste criteria |

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION**International Inventories**

| | TSCA | DSL | EINECS/ELINCS | ENCS | IECSC | KECL | PICCS | AICS |
|---|---------|-----|---------------|------|-------|------|-------|------|
| Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) 64742-65-0 | Present | X | 265-169-7 | X | X | X | X | X |
| Hydrotreated Distillates, Heavy Paraffinic 64742-54-7 | Present | X | 265-157-1 | X | X | X | X | X |

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

| | |
|--|----|
| Acute Health Hazard | No |
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA**U.S. State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

Florida

No listed ingredients are present

Massachusetts RTK

No listed ingredients are present

Minnesota RTK

No listed ingredients are present

New Jersey RTK

Lists petroleum oil, but this product does not contain hazardous ingredients.

Pennsylvania RTK

Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%.

Illinois DOL TSL

No listed ingredients are present

International Regulations

Mexico – Grade No information available.

Canada Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with Controlled Products Regulation

CONEG Metals Since cadmium, chromium, lead and mercury are not detectable and it does not exceed 100 ppm total in this product, it is compliant with CONEG Metals regulation.

EEC (Europe) This product is not known to be a dangerous good internationally.

| | |
|---------------|-------------------------|
| R-Phrases | R45: May Cause Cancer |
| S-Phrases | S53: Avoid Exposure S45 |
| Hazard Label | None |
| Danger Symbol | T : Toxic |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials

16. OTHER INFORMATION

| | |
|----------------------|-------------------|
| Prepared By | Safety Department |
| Issuing Date | 28-June -2010 |
| Revision Date | 28-June-2010 |
| Revision Note | Not applicable |

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS